



Eläkeliitto SM 26



Oil Pattern Distance	40	Reverse Brush Drop	38	Oil Per Board	41 ul
Forward Oil Total	10.537 mL	Reverse Oil Total	9.348 mL	Volume Oil Total	19.885 mL
Tank Configuration	Multi Tank	Tank A Conditioner	Terrain	Tank B Conditioner	Terrain

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	3L	3R	2	14	3	A	70	0.0	1.9	1.9	2870
2	4L	4R	2	14	3	A	66	1.9	5.8	3.9	2706
3	8L	8R	2	18	3	A	50	5.8	10.9	5.1	2050
4	11L	11R	3	18	3	A	57	10.9	18.5	7.6	2337
5	17L	17R	2	18	3	A	14	18.5	23.6	5.1	574
6	2L	2R	0	26	3	A	0	23.6	40.0	16.4	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	26	3	B	0	40.0	34.0	-6.0	0
2	14L	14R	2	18	3	B	26	34.0	28.9	-5.1	1066
3	10L	10R	2	18	3	B	42	28.9	23.8	-5.1	1722
4	8L	8R	3	18	3	B	75	23.8	16.2	-7.6	3075
5	8L	8R	2	14	3	B	50	16.2	12.3	-3.9	2050
6	3L	3R	1	14	3	B	35	12.3	10.4	-1.9	1435
7	2L	2R	0	14	3	B	0	10.4	0.0	-10.4	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 24:1 Reverse
Cleaner Ratio Back End Distance 59 Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle:Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	4.57	1.46	1.11	1.11	1.46	4.57

